



New Holland T7 -serie (TIER 4B STANDARD STEER)

7.165S - 7.175 - 7.190 - 7.210 - 7.225

- Ample choice in lifting capacity, PTOs and accessories to ensure they suit your work as much as possible
- No limitation of both the steering angle and ground clearance for maximum maneuverability
- Integrated rev counter in the tractor dashboard
- Can also be supplied with ECO and ECO-Twin PTOs
- Choice of PTOs and chain hangers in combination with front linkage system ex works

Afbeeldingen



Front linkage system design

- Front linkage 28 kN supported by means of side plates
- Front linkage 40 kN supported by means of side plates
- Front linkage 50 kN supported by means of side plates
- Top plate ready for fitting of front hydraulics, 7-pole connector and chain hooks
- Can also be supplied with heavy-duty lifting arm set
- Can be set to a single-acting, double-acting and transport position with the multi-valve supplied as standard
- Removable linkage arms with a transport, fixed and oscillation setting
- Comes with high quality Walterscheid lifting hooks
- Perfect design due to tractor-specific connections
- Supplied with a top link, balls and towing hook

Front PTO system design

- Integrated rev counter in the tractor dashboard
- Comes with an oil cooler as standard
- Output shaft can always be rotated over 60 degrees for maximum ease of connection
- PTO clutch engagement time variable to ensure smooth engagement
- Non-rotating output shaft in unloaded condition
- Oil immersed clutch plates ensures a long service life
- Supplied with protective cover for PTO stump

Additional Info

Front linkage system:

- Side plates are mounted to the top plate by means of welds (28, 40 kN)
- Side plates are mounted to the top plate by means of bolt connections (50 kN)
- Supplied professional installation manual in 4 languages simplifies installation

PTO system:

- Easily replaceable V-belt using clamp-on coupling
- Integrated oil system guarantees rapid PTO installation as it is independent of the tractor's hydraulic system
- PTO includes measuring points for easy locating of faults
- PTO is activated by means of the supplied switch for use inside the cabin
- Supplied professional installation manual in 4 languages simplifies installation

Other details:

- Can be supplied with front control set including an integrated height limitation for tractors compatible with SideWinder II version.