

John Deere 6R(C) -serie (TIER 4) 6090RC - 6100RC - 6110RC

- Front linkage can be set to a single-acting, double-acting and transport position with the multi-valve supplied as standard
- Includes removable linkage arms with a transport, fixed and oscillation
- Front linkage is supplied with a top link, balls and towing hook
 Output shaft can always be rotated over 60 degrees for maximum ease of connection
- PTO clutch engagement time variable to ensure smooth engagement

Afbeeldingen





















Front linkage system design

- Can be set to a single-acting, double-acting and transport position with the multi-valve supplied as standard
 Removable linkage arms with a transport, fixed and oscillation setting
 Comes with high quality Walterscheid lifting hooks
 Perfect design due to tractor-specific connections
 Supplied with a top link, balls and towing hook

Front PTO system design

- Output shaft can always be rotated over 60 degrees for maximum ease of connection PTO clutch engagement time variable to ensure smooth engagement
- Non-rotating output shaft in unloaded condition
- Oil immersed clutch plates ensures a long service life
- Supplied with protective cover for PTO stump

Additional Info

- Supplied professional installation manual in 4 languages simplifies installation
 Integrated oil system guarantees rapid PTO installation as it is independent of the tractor's hydraulic system
 PTO includes measuring points for easy locating of faults
 PTO is activated by means of the supplied switch for use inside the cabin